



**2008 SUPER STOCK  
INSPECTION SHEET**

**AASBD  
Car Number**

<b>Inspection Area</b>	<b>Description</b>	<b>Photos</b>	<b>Pass?</b>
<b>Steering Stop Installation</b>	Steering stop hardware per plans	Photo 1.3	_____
<b>Foot Brace Installation</b>	Foot brace hardware per plans	Photo 2.4	_____
<b>Kingpin Installation</b>	Bushing installed per plans Front kingpin washer stack per plans Rear kingpin washer stack per plans	Photo 3.5 & 3.7 Photo 3.17 Photo 3.26	_____ _____ _____
<b>Steering Hardware Installation</b>	Steering hardware per plans Cable pulleys installed per plans	Photos 4.7, 4.19, & 4.13(a) & (b) Photos 4.13(a) & (b)	_____ _____
<b>Steering Cabling Installation</b>	Cable pulley hardware per plans Axle eyebolt per plans Steering cable adjusters per plans Steering cable routing per plans Cable double-clamped per plans	Photo 5.5 Photo 5.12 Photos 5.17 & 5.31 Photos 5.23, 5.26, 5.37(a) & (b) Photo 5.36	_____ _____ _____ _____ _____
<b>Stabilizer Installation</b>	Bushing installed per plans Stabilizer assembly per plans	Photos 6.6 & 6.8 Photos 6.18 – 6.30	_____ _____
<b>Brake Pad Installation</b>	Brake pad installed per plans New brake pad installed	Photos 7.1 & 7.4	_____ _____
<b>Brake Installation</b>	Brake pedal hardware per plans Cable pulley installed per plans Brake plunger installed per plans Awning pulley hardware per plans Cable double-clamped per plans Brake cable routing per plans	Photos 8.4, 8.12 & 8.19 Photo 8.25 Photos 8.27 & 8.31 Photo 8.41 Photo 8.45 Photos 8.47 & 8.50	_____ _____ _____ _____ _____ _____
<b>Weight Bolt Installation</b>	Adjustable weight hardware per plans Fixed weight hardware per plans Ten pounds of adjustable weight with wing nut	Photo 9.10 Photo E20.6	_____ _____ _____
<b>Airfoil Installation</b>	Front axle airfoils installed per plans Rear axle airfoils installed per plans	Photos 10.1 & 10.3 Photos 10.6 & 10.8	_____ _____
<b>Shell Installation</b>	Front foam installed per plans Optional rear and side foam installed per plans Screw in nose of the shell Shell flush with bottom of floorboard Shell rear lip minimum of 1/4 inches No overspray on inside of shell	Photo 12.4 Photo E22.5 & E22.8 Photo 12.11  Photo E22.10	_____ _____ _____ _____ _____ _____
<b>Signage, Lettering &amp; Decoration</b>	Shell decals and decorations per plans All-American Soap Box Derby Number Title/National Sponsor(s) Local Race City Organization OR Rally Region All-American Soap Box Derby Logo	Photo 13.1 (all views) Photo 13.1 (all views) Photo 13.1 (all views) Photo 13.1 (all views) Photo 13.1 (all views)	_____ _____ _____ _____ _____
<b>Floorboard</b>	Thin layer of wax only		_____
<b>Axles</b>	2001 or newer		_____
<b>Wheel Base</b>	63-5/16 inches spindle to spindle		_____
<b>Errors in Construction</b>	Repairs must be completed within one hour		_____

The persons signing this document acknowledge that, as a condition precedent to participation in the All-American Soap Box Derby (AASBD) World Championship in Akron, Ohio, the cars of such winner must pass an inspection conducted in Akron, Ohio by the AASBD representatives chosen by and in the sole and absolute discretion of the AASBD. The inspection shall be conducted by the AASBD in accordance with the applicable rules, spirit, plans and specifications as the AASBD shall determine and it is understood and agreed that the decision of the AASBD regarding compliance with these items as well as qualification/disqualification of any car shall be final and binding upon all parties.

Local Race Director Signature

Date

Regional Director Signature

Date